

# sewoo

## 3-Inch Direct Thermal POS Printer

# SLK-TL100



- Printing speed and Compatibility
- Maximize productivity with Compact and Sleek design
- The simplest and efficient design for environments with limited space
- Reduce power consumption and cost through energy star certification
- High reliability mechanism: 1.5 Million of Cutter life and 160km of TPH Life



Compact Design



High Speed



Easy Maintenance




Barcode



Durable



Easy Loading



Paper Width



Light Weight



Energy Star

## APPLICATION



## SPECIFICATIONS



### PRINTER CHARACTERISTICS

#### Print Method

Direct thermal

#### Print Speed

Up to 6.2ips(160mm/sec)

#### Print Width

Up to 2.8" (72mm)

#### Resolution

Standard: 180 dpi

#### Power

Power type : External SMPS

AC : 100~240Vac 50/60Hz

DC : 24Vdc / 1.75A

#### Sensor

Standard: Paper end, Paper low,

Cover open

Optional: Black mark

#### Reliability

TPH life : 160km

MCBF : 60 Million lines

Cutter life : 2 Million cuts

#### Drawer port

2 Circuit(24V, 1A Max.)



### PHYSICAL CHARACTERISTICS

#### Dimension (W x D x H)

5.35" x 6.49" x 4.37"

(136 x 165 x 111mm)

#### Weight

1.3lb(0.6Kg)



### INTERFACES

#### Standard

USB(B type)+Serial(RS-232C\_9pin)

Built-in



### CERTIFICATIONS

CE, FCC, KC, UL/cUL, ENERGY STAR



### COLOR

Black, Ivory, Blue



### OPERATING CHARACTERISTICS

#### Operating Temperature

41 ~ 104°F(5 ~ 40°C)

#### Operating Humidity

10 ~ 90%

#### Storage Temperature

-4 ~ 140°F(-20 ~ 60°C)

#### Storage Humidity

10 ~ 90%



### MEDIA CHARACTERISTICS

#### Media Type

Thermal receipt paper

#### Media Width

3.11"(79mm)

#### Media Core Diameter

0.4"(12.5mm)

#### Media Roll Diameter

3.2"(ø 83mm)

#### Thickness

0.05~0.09mm



### SOFTWARE

#### Emulations

ESC/POS

#### Drivers

Windows Driver(XP ~, Server2003 ~),  
Windows CE & Mobile Driver (CE 4.2 ~,  
Mobile 5.0 ~), Linux Driver, Mac Driver,  
OPOS Driver, JavaPOS Driver, iOS SDK,  
Android(6.0 ~) SDK, Windows SDK,  
Windows CE SDK, Linux SDK



### BARCODES

#### 1D

EAN-8, EAN-13, Code 39, Code 93,

Code 128, ITF, UPC-A, UPC-E, Codabar

#### 2D

PDF 417, QR code, DATA MATRIX



### FONTS / GRAPHICS

#### Character Type

Font A(12x24), Font B(9x17),  
Chinese(Traditional/Simplified, 24x24),  
Korean(24x24), Japanese(24x24)

#### Characters per line (CPL)

Font A(12x24) : 42cpl,

Font B(9x17) : 56cpl,

Chinese/Korean/Japanese: 21cpl

#### Character set

95 Alphanumeric,

14 International,

128 x 18 Graphic



### ACCESSORIES

#### Standard

Power Adaptor 24Vdc / 1.75A

#### Option

Melody Box

# sewoo

#### Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

#### USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA\_Sales@miniprnter.com

#### México

Cuahtémoc, Mexico D.F.

T. +52-1-55-143893 M. +52-1-55-3232-9543

E. LA\_Sales@miniprnter.com

