

sewoo

HIGH SPEED DESKTOP THERMAL POS PRINTER

SLK-TE202II_L



- Energy star qualified for power efficiency
- High speed printing : 220mm/sec
- Paper width adjustable 50~82.5mm
- Support restick printing
- ESC/POS command compatible
- Wall mount installation available
- Printing notice accessory : Melody box, spillproof cover



Compact Design



High Speed




Easy Maintenance




Barcode



Durable



Easy Loading



Paper Width



Various interface



Paper Sensor



Restick

APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method

Direct thermal

Print Speed

Max. 220mm/sec(8.6ips)

Restick : Max. 160mm/sec(6.2ips)

Print Width

Max. 72mm(2.8")

Resolution

180dpi/203dpi

Power

Power type : External SMPS

AC : 100~240Vac 50/60Hz

DC : 24Vdc / 1.75A

Sensor

Standard: Paper End, Paper Low,
Cover Open

Option : Black Mark

Reliability

TPH life : 160km

Restick TPH life : 100km

MCBF : 60 Million lines

Cutter life : 1.8 Million cuts

Restick cutter life : 1 Million cuts

Drawer port

2 circuits(24V, 1A Max.)



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)

152 x 204 x 150mm

(5.98" x 8.03" x 5.90")

Weight

1.7Kg(3.74lb)



INTERFACES

Standard

USB(B type)

Option

Serial(RS-232C), Parallel(IEEE1284),

Ethernet, Wi-Fi(802.11 a/b/g/n),

Bluetooth Ver2.1(Movon,iOS)

Bluetooth Smart Ready

(Bluetooth5.2+BLE)



CERTIFICATIONS

CE, FCC, KC, UL/cUL,

ENERGY STAR



OPERATING CHARACTERISTICS

Operating Temperature

0 ~ 45°C(32 ~ 113°F)

Restick : 0 ~ 30°C(32 ~ 86°F)

Operating Humidity

35 ~ 80%

Storage Temperature

-20 ~ 60°C(-4 ~ 140°F)

Storage Humidity

10 ~ 90%



MEDIA CHARACTERISTICS

Media Type

Thermal receipt paper

Restick(Optional)

Media Width

50mm ~82.5mm(1.9~3.2")

Media Core Diameter

12.5mm ± 0.5mm(0.4")

Media Roll Diameter

ø 80mm(3.1")

Thickness

0.06~0.09mm



SOFTWARE

Emulations

ESC/POS Command compatible

Drivers

Windows Driver(XP ~, Server2003 ~),

Windows CE & Mobile Driver (CE 4.2 ~,

Mobile 5.0 ~), Linux Driver, Mac Driver,

OPOS Driver, JavaPOS Driver, iOS SDK,

Android(6.0 ~) SDK, Windows SDK,

Windows CE SDK, Linux SDK



BARCODES

1D

EAN-8, EAN-13, Code 39,

Code 93, Code 128, ITF,

UPC-A, UPC-E, Codabar

2D

PDF 417, QR code, DATA MATRIX



FONTS / GRAPHICS

Character Type

Font A(12x24), Font B(9x17),

Chinese(Traditional/Simplified, 24x24),

Korean(24x24), Japanese(24x24)

Characters per line (CPL)

Font A(12x24) : 42cpl,

Font B(9x17) : 56cpl,

Character set

95 Alphanumeric,

14 International,

128 x 18 Graphic



ACCESSORIES

Standard

Power Adaptor 24Vdc / 1.75A

Option

Melody Box, Spill proof cover

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA_Sales@miniprnter.com

México

Cuahtémoc, Mexico D.F.

T. +52-1-55-143893 M. +52-1-55-3232-9543

E. LA_Sales@miniprnter.com

