


2D Wireless Barcode Scanner NBS-SL856B



GENERAL FEATURES

- 0.3 Megapixels global shutter camera, fast reading speed 60fps/s.
- BT5.0 with transfer distance: 200M, 2600mAh battery capacity.
- Easy in reading 1D&2D code.(including colored, stained and fuzzy code)
- Plug and play, no driver installation. Support USB and RS232 interface.
- Distinctive cradle one-touch scanner search function to find the scanner immediately.
- Unique scanning barcode with vibration feedback, bring comfortable scanning experience.
- Compatible with Windows 7/8/10, iOS, Android, Linux system.
- Widely be used in warehouse, logistics, and retail stores.



NBS-SL856B

Specifications

Physical Characteristics

Dimensions	180mm x 110mm x 85mm
Weight	433g
Voltage/Current	5VDC+/-10%@500mA

Performance Characteristics

Image(Pixels)	640 pixels(H) x 480 pixels(V)
Light Source	Aiming : 617nm, LED illumination : 3,500K LED
Field of View	40°(H) x 32°(V)
Roll/Pitch/Yaw	Roll ±60° / Pitch ±65° / Yaw 360°
Print Contrast	25% minimum reflective difference
Interfaces Supported	USB,RS232
Motion Tolerances	≥2m/s
Decode Capability	1D UPC, EAN, Code 128, Code 39, Code 93, Code 11, Matrix 2 of 5, Codabar, Interleaved 2 of 5,MS Plessey, GS1 Databar, China Postal, Korean Postal, etc.
	2D PDF417, MicroPDF417 Data Matrix, Maxicode, QR Code, MicroQR, Aztec, Hanxin, etc.

User Environment

Operating Temperature	0° to 50° C
Storage Temperature	-40° to 70° C
Humidity	0% to 95% relative humidity, non-condensing
Shock Specifications	Designed to withstand 1.5m(5') drops
Ambient Light Immunity	100,000 Lux.

Decode Ranges

Code 39(20 mil)	20mm-370mm	Code 39 (5.13 mil)	30mm-120mm
PDF(6.88 mil)	10mm-170mm	DM (10 mil)	20mm-170mm
UPC-A 100%(13 mil)	20mm-360mm	QR (20 mil)	0mm-330mm



sewoo

Republic of Korea [Head Office/R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 / F. +82-31-624-5310 / E. sales@miniprinter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-859-992-5936

E. NA_Sales@miniprinter.com

México Office

Cuahtémoc, D.F. Mexico. CP 06500

T. +52-1-55-143893

M. +52-1-55-3232-9543

E. LA_sales@miniprinter.com

