

sewoo

Linerless Printer

SLK-SL103



- Supports Multiple Media Types (CPCL/ESCPOS/ZPL Command compatible)
- Space-saving vertical design with dual paper exit (Front&Top) Reduce waste improve efficiency with linerless printing.
- Order reminder alarm with volume control
- Specialized back-feed function
- Automatic media-specific print width adjustment
- Detects label removal to trigger next print



Built-in
Melody Box



Auto Width
Adjust



Paper
Saving (20%)



Takeoff
Sensor



APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method

Direct thermal(Front & Top Exit)

Print Speed

Linerless : 200mm/s, Receipt :250mm/s

Print Width

32 / 48 / 60 / 72 / 80 mm

Resolution

203 DPI

Power

Power type : External SMPS

AC : 100~240Vac 50/60Hz

DC : 24Vdc / 1.75A

Sensor

Standard: Paper end, Cover open,

Paper width Detection, Gap, Take-off

Reliability

TPH life : 160km

MCBF : 60 Million lines

Cutter life : 1.0 Million cuts

Drawer port

2 Circuit(24V, 1A Max.)



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)

57" x 57.5" x 83.8"

(145 x 146 x 213mm)

Weight

1.57kg



INTERFACES

Standard

USB(B type) + Ethernet

+ Serial(RS-232 9pin)

Option

U + S, U + E



CERTIFICATIONS

CE, FCC, KC, UL/cUL,

ENERGY STAR, Mfi



OPERATING CHARACTERISTICS

Operating Temperature

0 ~ 45°C

Operating Humidity

35 ~ 80%

Storage Temperature

-20 ~ 60°C

Storage Humidity

10 ~ 90%



MEDIA CHARACTERISTICS

Media Type

Thermal receipt paper, Blackmark,

Linerless(Restick, Permanent),

Gap Label, BluePaper

Media Width

40 / 58 / 62 / 80 / 83 mm

Media Core Diameter

Linerless : Min.1inch

Other : 12.5mm ± 0.5mm

Media Roll Diameter

Max. ø 105mm

Thickness

ESCPOS : 0.05 ~ 0.08 mm,

CPCL / ZPL : 0.06 ~ 0.15 mm



SOFTWARE

Emulations

CPCL/ESCPOS/ZPL

Command compatible

Drivers

Windows Driver(XP ~, Server2003 ~),

Linux Driver, Mac Driver, OPOS Driver,

JavaPOS Driver, iOS SDK, Android(6.0 ~)

SDK, Windows SDK, Linux SDK



BARCODES

1D

EAN-8, EAN-8(+2+5), EAN-13,

EAN-13(+2+5), Codabar, Code11,

Code39, Code93, Code128, ITF,

UPC-A(+2+5), UPC-E, UPC-E(+2+5),

Planet, etc

2D

QR, PDF417, MicroPDF417,

Maxicode, Datamatrix, Aztec,

RSS14, TLC39



COLOR

Black, Ivory



FONTS / GRAPHICS

Character Type

FontA(12x24), FontB(9x17),

Font0/1/2/4/5/6/7,

TTF Font0, FontA~H, FontGS

Font1~8, Asian Font(KOR, JPN,

CHN_GB2312, CHN_BIG5),

Resident TTF, Downloadable TTF,

Downloadable Bitmap

Characters per line (CPL)

Font A(12x24) :

21/32/40/48/ 53 columns

Font B(9x17) :

28/42/53/64/71 columns

Character set

Alpha Numeric Character : 95

Expanded Graphic :

128x18 Page (1 space page)

International Character : 14



ACCESSORIES

Melody box, 24V Internal/External Buzzer

Types Paper Guide :

Standard

83mm, 80mm, 62mm, 58mm, 40mm

Option

38mm

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA_Sales@miniprnter.com

México

Cuauhtémoc, Mexico D.F.

T. +52-1-55-143893 M. +52-1-55-3232-9543

E. LA_Sales@miniprnter.com

