

# sewoo

## DIRECT THERMAL POS PRINTER

# SLK-TL202II



- Energy star qualified for power efficiency
- High speed printing : 220mm/sec
- Paper width adjustable 50~82.5mm
- ESC/POS command compatible
- Accessories : Melody box, spillproof cover
- Wall mount installation available



Compact  
Design



High  
Speed



Easy  
Maintenance



Barcode



Durable



Easy  
Loading



Paper  
Width



Paper  
Sensor



Energy  
Star

## APPLICATION



## SPECIFICATIONS



### PRINTER CHARACTERISTICS

#### Print Method

Direct thermal

#### Print Speed

Up to 8.6ips(220mm/sec)

#### Print Width

Up to 2.8”(72mm)

#### Resolution

Standard: 180dpi

#### Power

Power type : External SMPS

AC : 100~240Vac 50/60Hz

DC : 24Vdc / 1.75A

#### Sensor

Standard: Paper End, Paper Low,  
Cover Open

Option : Black Mark

#### Reliability

TPH life : 160km

MCBF : 60 Million lines

Cutter life : 2 Million cuts

#### Drawer port

2 circuits(24V, 1A Max.)



### PHYSICAL CHARACTERISTICS

#### Dimension (W x D x H)

5.98” x 8.03” x 5.82”

(152 x 204 x 150mm)

#### Weight

3.74lb(1.7Kg)



### INTERFACES

#### Standard

USB(B type)+ Serial  
(RS-232C\_9pin) Built-in



### CERTIFICATIONS

CE, FCC, KC, UL/cUL,  
ENERGY STAR



### OPERATING CHARACTERISTICS

#### Operating Temperature

32 ~ 113°F(0 ~ 45°C)

#### Operating Humidity

35 ~ 80%

#### Storage Temperature

-4 ~ 140°F(-20 ~ 60°C)

#### Storage Humidity

10 ~ 90%



### MEDIA CHARACTERISTICS

#### Media Type

Thermal receipt paper

Linerless(Optional)

#### Media Width

1.9~3.2”(50mm ~82.5mm)

#### Media Core Diameter

0.4”(12.5mm ± 0.5mm)

#### Media Roll Diameter

3.1”(ø 80mm)

#### Thickness

0.05~0.09mm



### SOFTWARE

#### Emulations

ESC/POS Command compatible

#### Drivers

Windows Driver(XP ~, Server2003 ~),  
Windows CE & Mobile Driver (CE 4.2 ~,  
Mobile 5.0 ~), Linux Driver, Mac Driver,  
OPOS Driver, JavaPOS Driver, iOS SDK,  
Android(6.0 ~) SDK, Windows SDK,  
Windows CE SDK, Linux SDK



### BARCODES

#### 1D

EAN-8, EAN-13, Code 39,  
Code 93, Code 128, ITF,  
UPC-A, UPC-E, Codabar

#### 2D

PDF 417, QR code,  
DATA MATRIX



### FONTS / GRAPHICS

#### Character Type

Font A(12x24), Font B(9x17),  
Chinese(Traditional/Simplified, 24x24),  
Korean(24x24), Japanese(24x24)

#### Characters per line (CPL)

Font A(12x24) : 42cpl,

Font B(9x17) : 56cpl,

#### Character set

95 Alphanumeric,  
14 International,  
128 x 18 Graphic



### ACCESSORIES

#### Standard

Power Adaptor 24Vdc / 1.75A

#### Option

Melody Box, Spill proof cover

# sewoo

#### Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea  
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

#### USA, Inc.

Torrance, CA 90502, USA  
T. +1-310-617-7401  
E. NA\_Sales@miniprnter.com

#### México

Cuahtémoc, Mexico D.F.  
T. +52-1-55-143893 M. +52-1-55-3232-9543  
E. LA\_Sales@miniprnter.com

