

sewoo

Battery Cradle

# 4BC-20 4BC-30

- Competitive low price
- Excellent Compatibility
- Ultra Compact and Lightweight

Type	Battery cradle
InPut	AC 100 ~ 240Vac, 50~60Hz
Output	DC 9.5V / 4A
Charging Voltage	INPUT : DC 9.5V / 4A OUTPUT : DC 8.4V / 1.1A * 4
Charging Current	1.1A
Size	208 x 140 x 133 (mm)
Charging Time	2000mAh : 180Min. ± 10% 2600mAh : 220Min. ± 10% 5200mAh : 330Min. ± 10%



4BC-30

FOR LK-PB400L  
LK-PB400  
LK-PB30



4BC-20

FOR LK-PB20

## APPLICATION



## SPECIFICATIONS

Model	4BC-20	4BC-30
Compatible Model	LK-P20II, LK-P34L	LK-P30II, LK-P300, LK-P400
Battery	LK-PB20	LK-PB30, LK-PB400, LK-PB400L
Battery Capacity	7.4V / 2000mAh	7.2V / 3350mAh, 7.2V / 2500mAh, 7.2V / 5000mAh
Battery Image	 2000mAh	 LK-PB30 : 3350mAh LK-PB400 : 2500mAh
		 LK-PB400L : 5000mAh

## PRODUCT IMAGE



# sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea  
**T.** +82-31-8077-5000 **F.** +82-31-624-5310 **E.** sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA  
**T.** +1-310-617-7401

**E.** NA\_Sales@miniprnter.com

México

Cuahtémoc, Mexico D.F.

**T.** +52-1-55-143893 **M.** +52-1-55-3232-9543

**E.** LA\_Sales@miniprnter.com

