

sewoo

Board on the economic class being served with a great performance.

LK-P25II




- Economic but, excellent performance
- Ultra Compact and Lightweight
- Large Battery Capacity
- Wide Compatibility
- USB-C Type Charging Port
- S-MDM (Sewoo MDM) supported



Bluetooth



Barcode



Compact Design



Easy Maintenance



Improved Battery Life



Durable



Portable



Drop Resistant



Easy Loading



S-MDM Support

APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method
Direct thermal

Print Speed
80mm/sec

Print Width
48mm, 384 Dots/line

Resolution
203 DPI

Memory
8MB(Max 64MB), SRAM 8MB

Battery Voltage / Capacity
3.6V 3250mAh Li-ion
4Hrs Charging time(Charger)
6 Hrs Charging time(USB)

Standby Time
63 Hrs

Sensor
Paper end,
Cover open(Black mark sensor)

Reliability
TPH life : 50km



PHYSICAL CHARACTERISTICS

Dimension (W x L x D)
3.1" × 4.06" × 1.74"
(79 × 103.2 × 44.4mm)

Weight
190g - TBD



INTERFACES

Standard
USB C Type, Bluetooth Smart Ready
(Bluetooth5.2+BLE), NFC Tag



CERTIFICATIONS

KC, CE, FCC, IC, UL/cUL, Mfi,
UKCA, BCS, CB



OPERATING CHARACTERISTICS

Operating Temperature
-10 ~ 50°C

Operating Humidity
10 ~ 80%

Storage Temperature
-20 ~ 60°C

Storage Humidity
10 ~ 90%

Drop Rating
1.5m(set only), 1.8m(with case)

Dust-and Water-resistance Rating
IP54(with case)



BARCODES

1D
EAN-8, EAN-8(+2+5), EAN-13,
EAN-13(+2+5), Codabar, Code11,
Code39, Code93, Code128, ITF,
UPC-A(+2+5), UPC-E, UPC-E(+2+5),
Planet, etc

2D
QR, PDF417, MicroPDF417, Maxicode,
Datamatrix, Aztec, RSS14, TLC39



SOFTWARE

Emulations
ESC/POS, CPCL, ZPL
Command compatible

Drivers
Windows Driver(XP ~, Server2003 ~),
Window CE & Mobile Driver & SDK
(CE 4.2~, Mobile 5.0~), Linux Driver,
Mac Driver, OPOS Driver, JavaPOS
Driver, iOS SDK, Android(6.0 ~) SDK



MEDIA CHARACTERISTICS

Media Type
Thermal paper

Media Width
58mm

Media Core Diameter
12.5mm ± 0.5mm

Media Roll Diameter
Max. Ø 40mm

Thickness
0.06mm



FONTS / GRAPHICS

Character Type
FontA(12x24), FontB(9x17),
Font0/1/2/4/5/6/7, TTF Font0, FontA~H,
FontGS, Font1~8, Asian Font(KOR, JPN,
CHN_GB2312, CHN_BIG5), Resident TTF,
Downloadable TTF, Downloadable Bitmap

Characters per Line (CPL)
Font A(12x24): 32 columns,
Font B(9x17): 42 columns

Character Set
Alpha numeric character: 95
Expanded graphic:
128*18 page(1 space page)
International character: 14



ACCESSORIES

Standard
Thermal Roll Paper,
Belt Clip & Battery Cover
AC/DC Adaptor 5VDC

Optional
Carrying Case (with Belt Clip),
Shoulder Strap, IP54 Case

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA
T. +1-310-617-7401
E. NA_Sales@miniprnter.com

México

Cuahtémoc, Mexico D.F.
T. +52-1-55-143893 M. +52-1-55-3232-9543
E. LA_Sales@miniprnter.com

