

# sewoo

## Robust and durable label mobile printers

# LK-P30II



- Fast Print Speed
- Excellent Compatibility
- Quick and easy to support peel mode
- Rugged design for Drop resistant
- Durable and resistant to water and dust
- S-MDM (SSM & SCM)
- Accessories : Shoulder Strap, Car Charger



WIFI



Bluetooth



Barcode



S-MDM  
Support



Compact  
Design



Easy  
Maintenance



Improved  
Battery Life



Durable



Fast  
Speed



Portable



Rugged  
Design



Drop  
Resistant



Easy  
Loading

## APPLICATION



## SPECIFICATIONS



### PRINTER CHARACTERISTICS

#### Print Method

Direct thermal

#### Print Speed

100mm/sec

#### Print Width

72mm, 576 Dots/line

#### Resolution

203 dpi (8dots/mm, 0.125 Pitch)

#### Memory

16MB(Max.32MB) Flash,

8MB SDRAM

#### Battery Voltage / Capacity

7.4V 2600mAh Li-ion,

7.2V 3350mAh Li-ion

#### Battery Charge Time

3.3Hrs (2600mAh),

4Hrs (3350mAh)

#### Standby Time

100Hrs (2600mAh),

90Hrs (3350mAh)

#### Sensor

Paper end, Black mark,

Cover open, Gap

#### Reliability

TPH life : 50km



### PHYSICAL CHARACTERISTICS

#### Dimension (W x L x D)

4.72"×5.98"×2.75"

(120×152×70mm)

#### Weight

640g (with Battery)



### INTERFACES

#### Standard

USB, Serial(RS-232C)

#### Option

Wi-Fi(802.11a/b/g/n),

Bluetooth Smart Ready

(Bluetooth5.2+BLE)



### CERTIFICATIONS

KC, CE, FCC, IC, UL/cUL, Mfi,

UKCA, BCS, CB



### OPERATING CHARACTERISTICS

#### Operating Temperature

-10 ~ 50°C

#### Operating Humidity

10 ~ 80%

#### Storage Temperature

-20 ~ 60°C

#### Storage Humidity

10 ~ 90%

#### Dust-and Water-resistance Rating

IP42, IP54(with case) certified

#### Drop Rating

1.2m(set only), 1.8m(with case)



### BARCODES

#### 1D

EAN-8, EAN-8(+2+5), EAN-13,

EAN-13(+2+5), Codabar, Code11,

Code39, Code93, Code128, ITF,

UPC-A(+2+5), UPC-E, UPC-E(+2+5),

Planet, etc

#### 2D

QR, PDF417, MicroPDF417, Maxicode,

Datamatrix, Aztec, RSS14, TLC39



### SOFTWARE

#### Emulations

ESC/POS, CPCL, ZPL

#### Drivers

Windows Driver(XP ~, Server2003 ~),

Window CE & Mobile Driver & SDK

(CE 4.2~, Mobile 5.0~), Linux Driver,

Mac Driver, OPOS Driver, JavaPOS

Driver, iOS SDK, Android(6.0 ~) SDK



### MEDIA CHARACTERISTICS

#### Media Type

Thermal Receipt/Label

#### Media Width

25 ~ 80mm

#### Media Core Diameter

12.5mm ± 0.5mm

#### Media Roll Diameter

Max. Ø 56mm

#### Thickness

0.06 ~ 0.16mm



### FONTS / GRAPHICS

#### Character Type

FontA(12x24), FontB(9x17),

Font0/1/2/4/5/6/7, TTF Font0, FontA~H,

FontGS, Font1~8, Asian Font(KOR, JPN,

CHN\_GB2312, CHN\_BIG5), Resident TTF,

Downloadable TTF, Downloadable Bitmap

#### Characters per Line (CPL)

Font A(12x24): 48 columns,

Font B(9x17): 64 columns

#### Character Set

Alpha numeric character : 95

Expanded graphic :

128\*18 page(1 space page)

International character : 14



### ACCESSORIES

#### Standard

USB Cable, Battery Pack, Serial Cable

Thermal Roll Paper, Belt Buckle,

Battery Charger (8.4V)

#### Optional

Battery Cradle (P30), Vehicle Charger,

Leather Case, Shoulder Trap, RTC

4 Bay Cradle

# sewoo

#### Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

#### USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA\_Sales@miniprnter.com

#### México

Cuahtémoc, Mexico D.F.

T. +52-1-55-143893 M. +52-1-55-3232-9543

E. LA\_Sales@miniprnter.com

