

sewoo

3-Inch POS Printer

# SLK-TS100



- High Performance Easy Maintenance
- Easy maintenance with Jam release lever
- Easy maintenance for paper jam
- High speed printing at 8.6ips (220mm/sec)
- Ergonomic Design Entry-level Printer
- Simple and easy replacement of components including head, motor, cutter, PCB, etc
- Ideal for top exit printing with wall mount



Compact Design



Easy Maintenance



High Speed




Barcode



Durable



Easy Loading



Paper Width

## APPLICATION



## SPECIFICATIONS

### **PRINTER CHARACTERISTICS**

**Print Method**  
Direct thermal

**Print Speed**  
220mm/sec

**Print width**  
2.83"  
(72mm, adjustable by commands)

**Resolution**  
203 dpi

**Power**  
Power type : External SMPS  
AC : 110~220Vac 50/60Hz  
DC : 24Vdc / 2.5A

**Sensor**  
Paper end, Cover open

**Reliability**  
TPH life : 100km  
MCBF : 80 Million lines  
Cutter life : 1.5 Million cuts

**Drawer port**  
circuit (24V, Max. 1A )

### **PHYSICAL CHARACTERISTICS**

**Dimension (W x D x H)**  
5.59" x 7.28" x 5.35"  
(142 x 185 x 136mm)

**Weight**  
2.25b(1.02Kg)

### **INTERFACES**

1. USB+SEIRAL(RS-232C\_9pin)+RJ45 serial+Ethernet Built-in
2. USB+SEIRAL(RS-232C\_9pin)+RJ45 serial (korea standard)

### **CERTIFICATIONS**

CE, FCC, KC,ENERGY STAR,  
ROHS

### **OPERATING CHARACTERISTICS**

**Operating Temperature**  
32 ~ 113°F(0 ~ 45°C)

**Operating Humidity**  
10 ~ 80RH%

**Storage Temperature**  
14 ~ 140°F(-10 ~ 60°C)

**Storage Humidity**  
10 ~ 90RH%

### **MEDIA CHARACTERISTICS**

**Media Type**  
Thermal receipt paper

**Media Width**  
79.5±0.5mm

**Media Core Diameter**  
0.49~0.5"(12.5mm ± 0.5mm )

**Media Roll Diameter**  
3.1"(Max. ø 80mm)

**Thickness**  
0.05~0.08mm

### **SOFTWARE**

**Emulations**  
ESC/POS Command compatible

**Drivers**  
Windows Driver(XP~, Server2003~),  
Linux Driver, Mac Driver, OPOS Driver,  
JavaPOS Driver

**SDK**  
Android(6.0~) SDK, Windows SDK

### **BARCODES**

**1D**  
EAN-8, EAN-13, Code 39,  
Code 93, Code 128, ITF,  
UPC-A, UPC-E, Codabar

**2D**  
PDF 417, QR code

### **FONTS / GRAPHICS**

**Character Type**  
Font A(12x24), Font B(9x17),  
Chinese(Traditional/Simplified, 24x24),  
Korean(24x24), Japanese(24x24)

**Characters per line (CPL)**  
· 180dpi  
Font A(12x24) : 42cpl,  
Font B(9x17) : 59cpl,  
· 203dpi  
Font A(12x24) : 48,  
Font B(9x17) : 64cpl  
Chinese/Korean/Japanese: 24cpl

**Character set**  
95 Alphanumeric,  
16 International,  
128 x 18 Graphic

### **ACCESSORIES**

**Built in melody standard**

1. SLK-TS100E(USB + Serial + Ethernet)  
: Built in melody
2. Korea standard  
(USB+SEIRAL(RS-232C\_9pin)+RJ45 serial)  
: Built in melody

# sewoo

#### Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea  
**T.** +82-31-8077-5000 **F.** +82-31-624-5310 **E.** sales@miniprinter.com

www.miniprinter.com

#### USA, Inc.

Torrance, CA 90502, USA  
**T.** +1-310-617-7401  
**E.** NA\_Sales@miniprinter.com

#### México

Cuahtémoc, Mexico D.F.  
**T.** +52-1-55-143893 **M.** +52-1-55-3232-9543  
**E.** LA\_Sales@miniprinter.com

