

# sewoo

## 3-Inch POS Printer

# SLK-TS200




- Simple and sleek design
- High Performance Easy Maintenance
- Wheel-type paper jam control
- High speed printing at 250mm/sec(9.8ips)
- Visible wireless connectivity status
- Ideal for top exit printing with wall mount
- Simple and easy replacement of components including head, motor, cutter, PCB, etc



WIFI



Bluetooth



Compact  
Design



Easy  
Maintenance




High  
Speed




Barcode



Durable



Easy  
Loading



Paper  
Width

## APPLICATION



## SPECIFICATIONS

### **PRINTER CHARACTERISTICS**

**Print Method**  
Direct thermal

**Print Speed**  
Up to 250mm/sec(9.8ips)

**Print Width**  
Up to 72mm(2.8")

**Resolution**  
203dpi

**Power**  
Power type : External SMPS  
AC : 110~220Vac 50/60Hz  
DC : 24Vdc / 2.5A

**Sensor**  
Paper end, Cover open

**Reliability**  
TPH life : 150km  
MCBF : 80 Million lines  
Cutter life : 2.0 Million cuts  
Cutter method: Partial / Full cut  
(Command or tool setting)

**Speaker**  
3type built in melody

**Drawer port**  
1 circuit(24V, Max. 1A)

### **PHYSICAL CHARACTERISTICS**

**Dimension (W x D x H)**  
174×136×132mm  
(6.85"×5.35"×5.19")

**Weight**  
1.04Kg(2.3lb)

### **INTERFACES**

**Standard**  
USB(B type)+Serial  
(RS-232C\_9pin)+Ethernet Built-in

**Optional**  
Bluetooth Smart Ready  
(Bluetooth5.0+BLE)  
or WiFi(802.11a/b/g/n)

### **CERTIFICATIONS**

KC, CE, FCC, IC, CB,  
cTUVus, Energy Star

### **OPERATING CHARACTERISTICS**

**Operating Temperature**  
32 ~ 113°F(0 ~ 45°C)

**Operating Humidity**  
10 ~ 80%

**Storage Temperature**  
4 ~ 140°F(-10 ~ 60°C)

**Storage Humidity**  
10 ~ 90%

### **MEDIA CHARACTERISTICS**

**Media Type**  
Thermal receipt paper  
Black mark paper

**Media Width**  
Max.58mm/80mm

**Media Core Diameter**  
12.5mm ± 0.5mm

**Media Roll Diameter**  
Max. ø 83mm

**Thickness**  
0.05~0.08mm

### **SOFTWARE**

**Emulations**  
ESC/POS Command compatible

**Drivers**  
Windows Driver(XP ~, Server2003 ~),  
Linux Driver, Mac Driver, OPOS Driver,  
JavaPOS Driver

**SDK**  
Android SDK, iOS SDK, Windows SDK

### **BARCODES**

**1D**  
EAN-8, EAN-13, Code 39, Code 93,  
Code 128, ITF, UPC-A, UPC-E, Codabar

**2D**  
PDF 417, QR code

### **FONTS / GRAPHICS**

**Character Type**  
Font A(12x24), Font B(9x17),  
Chinese(Traditional/Simplified, 24x24),  
Korean(24x24), Japanese(24x24)

**Characters per line (CPL)**  
· 180dpi  
Font A(12x24) : 42/30cpl  
Font B(9x17) : 59/40cpl  
· 203dpi  
Font A(12x24) : 48/35cpl  
Font B(9x17) : 64/46cpl

**Character set**  
95 Alphanumeric,  
16 International,  
128 x 18 Graphic

### **ACCESSORIES**

**Optional**  
Melody box, 24V Buzzer,  
2inch Paper Guide

# sewoo

#### Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea  
**T.** +82-31-8077-5000 **F.** +82-31-624-5310 **E.** sales@miniprnter.com

www.miniprnter.com

#### USA, Inc.

Torrance, CA 90502, USA  
**T.** +1-310-617-7401  
**E.** NA\_Sales@miniprnter.com

#### México

Cuahtémoc, Mexico D.F.  
**T.** +52-1-55-143893 **M.** +52-1-55-3232-9543  
**E.** LA\_Sales@miniprnter.com

