

# sewoo

## Ultra Compact Mobile Printer

# LK-P22



- Fast Print Speed : 100mm/sec
- Ultra Compact and Lightweight
- Excellent Compatibility
- NFC for easy Bluetooth pairing
- Durable and resistant to water and dust
- S-MDM (SSM & SCM)
- Accessories : Belt Clip, Belt Bracket & Strap, Car Charger



WIFI



Bluetooth



Barcode



Compact Design



Easy Maintenance



Improved Battery Life



Durable



Portable



Fast Speed



NFC



S-MDM Support



Drop Resistant



Easy Loading

## APPLICATION



## SPECIFICATIONS



### PRINTER CHARACTERISTICS

**Print Method**  
Direct thermal

**Print Speed**  
100m/sec

**Print Width**  
48mm, 384dots/line

**Resolution**  
203 DPI

**Memory**  
8MB(Max 64MB)  
SDRAM 8MB

**Battery Voltage / Capacity**  
7.4V 1450mAh Li-ion  
1.7 Hrs Charging time  
36 Hrs Stand-by

**Sensor**  
Paper end, Cover open

**Reliability**  
TPH life : 50km



### PHYSICAL CHARACTERISTICS

**Dimension (W x L x D)**  
3.14" × 4.70" × 1.73"  
(80 × 119.4 × 44mm)

**Weight**  
242.5g(With Battery)



### INTERFACES

**Standard**  
USB

**Optional**  
Wi-Fi(802.11a/b/g/n), Bluetooth  
Smart Ready(Bluetooth5.2+BLE)



### CERTIFICATIONS

KC, CE, FCC, IC, UL/cUL, M, UKCA,  
BCS, CB



### OPERATING CHARACTERISTICS

**Operating Temperature**  
-10 ~ 50°C

**Operating Humidity**  
10 ~ 80%

**Storage Temperature**  
-20 ~ 60°C

**Storage Humidity**  
10 ~ 90%

**Dust-and Water-resistance Rating**  
IP42 certified

**Drop Rating**  
1.5m(set only), 1.8m(with case)



### BARCODES

**1D**  
EAN-8, EAN-8(+2+5), EAN-13,  
EAN-13(+2+5), Codabar, Code11,  
Code39, Code93, Code128, ITF,  
UPC-A(+2+5), UPC-E, UPC-E(+2+5),  
Planet, etc

**2D**  
QR, PDF417, MicroPDF417, Maxicode,  
Datamatrix, Aztec, RSS14, TLC39



### SOFTWARE

**Emulations**  
ESC/POS, CPCL, ZPL Command  
compatible

**Drivers**  
Windows Driver(XP ~, Server2003 ~),  
Window CE & Mobile Driver & SDK  
(CE 4.2~, Mobile 5.0~), Linux Driver,  
Mac Driver, OPOS Driver, JavaPOS  
Driver, iOS SDK, Android(6.0 ~) SDK



### MEDIA CHARACTERISTICS

**Media Type**  
Thermal Receipt

**Media Width**  
58mm

**Media Core Diameter**  
12.5mm ± 0.5mm

**Media Roll Diameter**  
Max. Ø 40mm

**Thickness**  
0.06mm



### FONTS / GRAPHICS

**Character Type**  
FontA(12x24), FontB(9x17),  
Font0/1/2/4/5/6/7, TTF Font0,  
FontA~H, FontGS, Font1~8,  
Asian Font(KOR, JPN, CHN\_GB2312,  
CHN\_BIG5), Resident TTF, Downloadable  
TTF, Downloadable Bitmap

**Characters per Line (CPL)**  
Font A(12x24): 32 columns  
Font B(9x17): 42columns

**Character Set**  
Alpha numeric character : 95  
Expanded graphic : 128\*18 page(1 space page)  
International character : 14



### ACCESSORIES

**Standard**  
USB Cable, Battery Charger(8.4V)  
Battery Pack, Thermal Roll Paper,  
Belt Clip

**Optional**  
Set cradle, Battery cradle,  
Leather case + Shoulder Strap

# sewoo

#### Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea  
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

#### USA, Inc.

Torrance, CA 90502, USA  
T. +1-310-617-7401  
E. NA\_Sales@miniprnter.com

#### México

Cuahtémoc, Mexico D.F.  
T. +52-1-55-143893 M. +52-1-55-3232-9543  
E. LA\_Sales@miniprnter.com

