

sewoo

Cost-effective and Light weight Receipt/Label Printer

LK-P41



- Competitive low price
- Excellent Compatibility
- Ultra Compact and Lightweight
- Full support of Power Save Mode
- Durable and Resistant to Water and Dust
- CPU Upgrade to Renesas : 20~30% improvement in data processing performance.
- S-MDM (SSM & SCM)
- Accessories : Shoulder Strap, Car Charger, Leather Case



WIFI



Bluetooth



Barcode



Compact Design



Easy Maintenance



Improved Battery Life



Durable



Portable



S-MDM Support



Drop Resistant



Easy Loading

APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method

Direct thermal

Print Speed

80mm/sec

Print Width

104mm, 832 Dots/line

Resolution

203 dpi (8dots/mm, 0.125 Pitch)

Memory

FLASH : 8MB (Max 64MB)

SDRAM : 16MB (Max 64MB)

Battery Voltage / Capacity

7.2V 3350mAh, 6700mAh

4.0Hrs Charging time(3350mAh)

7.5Hrs Charging time(6700mAh)

180Hrs Stand-by(6700mAh)

Sensor

Paper end, Gap,

Black mark, Cover open

Reliability

TPH life : 50km



PHYSICAL CHARACTERISTICS

Dimension (W x L x D)

5.87" × 6.37" × 2.75"

(149 × 162 × 70mm)

Weight

610g (with 3350mAh battery)



INTERFACES

Standar

USB, Serial(RS-232C)

Optional

Wi-Fi(802.11a/b/g/n),

Bluetooth Smart Ready

(Bluetooth5.2+BLE)



CERTIFICATIONS

KC, CE, FCC, IC, UL/cUL, M,

UKCA, BCS



OPERATING CHARACTERISTICS

Operating Temperature

-10 ~ 50°C

Operating Humidity

35 ~ 80%

Storage Temperature

-20 ~ 60°C

Storage Humidity

10 ~ 90%

Dust and Water Resistance Rating

IP54(with case) certified

Drop Rating

1.2m(set only), 1.8m(with case)



BARCODES

1D

EAN-8, EAN-8(+2+5), EAN-13,

EAN-13(+2+5), Codabar, Code11,

Code39, Code93, Code128, ITF,

UPC-A(+2+5), UPC-E, UPC-E(+2+5),

Planet, etc

2D

QR, PDF417, MicroPDF417, Maxicode,

Datamatrix, Aztec, RSS14, TLC39



SOFTWARE

Emulations

ESC/POS, CPCL, ZPL Command compatible

Drivers

Windows Driver(XP ~, Server2003 ~),

Window CE & Mobile Driver & SDK

(CE 4.2~, Mobile 5.0~), Linux Driver,

Mac Driver, OPOS Driver, JavaPOS

Driver, iOS SDK, Android(6.0 ~) SDK



MEDIA CHARACTERISTICS

Media Type

Thermal Receipt/Label

Media Width

50~112mm

Media Core Diameter

12.5mm ± 0.5mm

Media Roll Diameter

Max. Ø 56mm

Thickness

0.06 ~ 0.16mm



FONTS / GRAPHICS

Character Size

FontA(12x24), FontB(9x17),

Font0/1/2/4/5/6/7, TTF Font0, FontA~H,

FontGS, Font1~8, Asian Font(KOR, JPN,

CHN_GB2312, CHN_BIG5), Resident TTF,

Downloadable TTF, Downloadable Bitmap

Characters per Line (CPL)

Font A(12x24): 69 columns

Font B(9x17): 92 columns

Character Set

Alpha numeric character : 95

Expanded graphic :

128*18 page(1 space page)

International character : 14



ACCESSORIES

Standard

USB Cable, Serial Cable,

Battery Pack, Thermal Roll Paper,

Battery Charger (8.4V/1A)

Optional

Battery Cradle (P41)

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA_Sales@miniprnter.com

México

Cuahtémoc, Mexico D.F.

T. +52-1-55-143893 M. +52-1-55-3232-9543

E. LA_Sales@miniprnter.com

