

sewoo

Compact size and Enhanced usability

# SLK-CB125



- Compact size cube printer
- Structure for easy maintenance
- Design for enhanced usability
- Convenient jam control structure
- Compact footprint to help easily fit on the counter.
- Supports flexible printing exit way Front exit or top exit.
- Ideal for kitchen/bar printer with melody box(Kitchen buzzer)



Compact Design



Fast Speed



Bluetooth



Easy Maintenance



WiFi



Barcode



Triple interface



Easy Loading

82.5mm

Paper Width

## APPLICATION



## SPECIFICATIONS



### PRINTER CHARACTERISTICS

#### Print Method

Direct thermal

#### Print Speed

250mm/sec(9.8ips)

#### Print Width

80mm(640 Dots/Line)

#### Resolution

203 DPI

#### Power

Power type : External SMPS

AC : 110~220Vac 50/60Hz

DC : 24Vdc / 2.5A

#### Sensor

Paper end, Cover open,

Paper low (Front-Exit Mode Only)

#### Reliability

TPH life : 150km

MCBF : 80 Million lines

Cutter life : 2.0 Million cuts

Cutter method: Partial / Full cut

#### Drawer port

2 circuit(24V, Max. 1A)



### PHYSICAL CHARACTERISTICS

#### Dimension (W x D x H)

125 × 131.5 × 125mm

(4.92" × 5.17" × 4.92")

#### Weight

0.91kg



### INTERFACES

#### Standard

1 : USB(B type)+Serial

(RS-232C\_9pin)+Ethernet Built-in

2 : USB(B type)+Serial

(RS232C-9Pin)+RJ45(Serial)

#### Optional

Bluetooth Smart Ready

(Bluetooth5.0+BLE) or

WiFi(802.11 a/b/g/n) B/T, WF combo



### CERTIFICATIONS

KC, CE, FCC, IC, CB, NRTL



### OPERATING CHARACTERISTICS

#### Operating Temperature

0 ~ 45°C

#### Operating Humidity

10 ~ 80%

#### Storage Temperature

-10 ~ 60°C

#### Storage Humidity

10 ~ 90%



### MEDIA CHARACTERISTICS

#### Media Type

Thermal receipt paper

#### Media Width

58mm / 80mm / 82.5mm

#### Media Core Diameter

12.5mm ± 0.5mm

#### Media Roll Diameter

Max. ø 83mm

#### Thickness

0.06~0.08mm



### SOFTWARE

#### Emulations

ESC/POS Command compatible

#### Drivers

Windows Driver(XP ~, Server2003 ~),

Linux Driver, Mac Driver, OPOS Driver,

JavaPOS Driver

#### SDK

Android SDK, iOS SDK, Windows SDK



### BARCODES

#### 1D

EAN-8, EAN-13, Code 39, Code 93,

Code 128, ITF, UPC-A, UPC-E, Codabar

#### 2D

PDF 417, QR code



### FONTS / GRAPHICS

#### Character Type

Font A(12x24), Font B(9x17),

Chinese(Traditional/Simplified, 24x24),

Korean(24x24), Japanese(24x24)

#### Characters per line (CPL)

· 180 DPI

Font A(12x24) : 46/42/30 columns

Font B(9x17) : 62/59/40 columns

· 203 DPI

Font A(12x24) : 53/48/35 columns

Font B(9x17) : 71/64/46 columns

#### Character set

Alpha Numeric Character : 95

Expend Graphic : 128x18 Page (1 space page)

International Character : 16



### ACCESSORIES

#### Standard

Power Adaptor 24Vdc / 2.5A

#### Optional

Melody Box, 24V Buzzer, Paper Guide

# sewoo

#### Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

#### USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA\_Sales@miniprnter.com

#### México

Cuahtémoc, Mexico D.F.

T. +52-1-55-143893 M. +52-1-55-3232-9543

E. LA\_Sales@miniprnter.com

