

sewoo

Reliable Barcode & Tag Printer

LK-B230II



- Stable & durable, cost savings
- Easy to use and maintenance
- Standard interfaces port
- Thermal transfer and direct thermal printing
- Paper width adjustable from 18mm to 118mm



WIFI



Bluetooth



Compact
Design



Easy
Replacement



Barcode



Durable



Easy
Loading

APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method
Direct thermal

Print Speed
102mm/sec

Print Width
104mm (4.1")

Resolution
300 DPI (12 dots/mm)

Memory
Main Flash 1MB
SDRAM 16MB
FONT Flash 8MB

Sensor
Gap, Black mark, Cover open,
Ribbon encoder

Power
Type : External SMPS
AC : 100~240Vac, 1.5A, 50~60Hz
DC : 24Vdc 2.5A

Auto-cutter(Optional)
Type : Guillotine
Life : 200,000 Cuts, Max 20 cycle/1 min



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)
8.46" x 11.3" x 9.09"
(215 x 287 x 231 mm)

Weight (Kg)
3.6kg



MEDIA CHARACTERISTICS

Media Type
Roll, Fanfold, Tag, Blackmark,
Continuous, Gap, Notch Sensor

Media Width
18 ~118mm

Media Core Diameter
25.4mm (1") or Ø 38.1mm(1.5")

Media Roll Diameter
Up to 127mm (5")

Ribbon Width
33~110mm (1.3 ~ 4.3")

Ribbon Length
360M, Ø 67mm (2.63")

Thickness
0.065~0.20mm



OPERATING CHARACTERISTICS

Operating Temperature
0 ~ 40°C

Operating Humidity
10 ~ 90%

Storage Temperature
-20 ~ 60°C

Storage Humidity
10 ~ 90%



BARCODES

1D
Code39, Code128 with subsets
A/B/C/Auto, UCC/EAN-128, Code93,
Codabar, Interleaved 2 of 5, UPC-A,
UPC-E, UPC-A and E with 2 or 5 digit
extension, EAN-8, EAN-13, EAN-8 and
13 with 2 or 5 digit extensions,
Postnet, Plessey, MSI-3, German Post
CodeLogmars, Code11,
UPC_Interleaved 2 of 5, Industrial
2 of 5, Standard 2 of 5, Planet, ANSI,
Logmars

2D
MaxiCode, PDF 417, Data Matrix,
QR Code, MicroPDF417, AZTEC,
Code 49, CODABLOCK, RSS



SOFTWARE

Emulations
ZPL II Command compatible

Drivers
Windows Driver
Linux Driver
Mac Driver

SDK
Windows SDK
Android SDK
iOS SDK



INTERFACES

Standard
USB, Serial(RS-232C), Ethernet

Option
Wi-Fi(802.11a/b/g/n),
Bluetooth Smart Ready
(Bluetooth4.2+BLE)



CERTIFICATIONS

KCC, CE, CB



FONTS / GRAPHICS

EPL II
6 bitmapped
8x12, 10x16, 12x20, 14x24,
32x48, 24x24(KSC5601)

ZPL II
9 bitmapped
5×9, 7×11, 10×18, 10x18, 15×28,
13×26, 40×60, 13x21, 24x24
2 smooth scalable(English, Korean)



ACCESSORIES

Standard
Power Cord, Power Supply,
Interface Cable(USB)

Optional
Peeler, Auto Cutter,
External Paper Supply

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea
T. +82-31-8077-5000 **F.** +82-31-624-5310 **E.** sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA
T. +1-310-617-7401
E. NA_Sales@miniprnter.com

México

Cuahtémoc, Mexico D.F.
T. +52-1-55-143893 **M.** +52-1-55-3232-9543
E. LA_Sales@miniprnter.com

