

# sewoo

## HIGH SPEED DESKTOP THERMAL POS PRINTER

# SLK-TE203



- Energy star qualified for power efficiency
- High speed printing : 300mm/sec
- Paper width adjustable 50~82.5mm
- ESC/POS command compatible
- Printing notice accessory : Melody box
- Wall mount installation available



Compact Design



High Speed




Easy Maintenance




Barcode



Durable



Easy Loading



Paper Width



Various interface



Paper Sensor



Energy Star

## APPLICATION



## SPECIFICATIONS



### PRINTER CHARACTERISTICS

#### Print Method

Direct thermal

#### Print Speed

300mm/sec

#### Print Width

Up to 2.8" (72mm)

#### Resolution

Standard: 180dpi

#### Power

Power type : External SMPS

AC : 100~240Vac 50/60Hz

DC : 24Vdc / 1.75A

#### Sensor

Standard: Paper End, Paper Low, Cover Open

Option : Black Mark

#### Reliability

TPH life : 160km

MCBF : 60 Million lines

Cutter life : 2 Million cuts

#### Drawer port

2 circuits(24V, 1A Max.)



### PHYSICAL CHARACTERISTICS

#### Dimension (W x D x H)

5.98" x 8.03" x 5.82"

(152 x 204 x 155mm)

#### Weight

3.74lb(1.7Kg)



### INTERFACES

#### Standard

USB(B type)

#### Option

Serial(RS-232C), Parallel(IEEE1284),

Ethernet, Wi-Fi(802.11 a/b/g/n),

Bluetooth Ver2.1(Movon,iOS)

Bluetooth Smart Ready

(Bluetooth5.2+BLE)



### CERTIFICATIONS

CE, FCC, KC, UL/cUL,

ENERGY STAR



### OPERATING CHARACTERISTICS

#### Operating Temperature

32 ~ 113°F(0 ~ 45°C)

#### Operating Humidity

35 ~ 80%

#### Storage Temperature

-4 ~ 140°F(-20 ~ 60°C)

#### Storage Humidity

10 ~ 90%



### MEDIA CHARACTERISTICS

#### Media Type

Thermal receipt paper

Linerless(Optional)

#### Media Width

1.9~3.2"(50mm ~82.5mm)

#### Media Core Diameter

0.4"(12.5mm ± 0.5mm)

#### Media Roll Diameter

3.1"(ø 80mm)

#### Thickness

0.06~0.09mm



### SOFTWARE

#### Emulations

ESC/POS Command compatible

#### Drivers

Windows Driver(XP ~, Server2003 ~),

Windows CE & Mobile Driver (CE 4.2 ~,

Mobile 5.0 ~), Linux Driver, Mac Driver,

OPOS Driver, JavaPOS Driver, iOS SDK,

Android(6.0 ~) SDK, Windows SDK,

Windows CE SDK, Linux SDK



### BARCODES

#### 1D

EAN-8, EAN-13, Code 39,

Code 93, Code 128, ITF,

UPC-A, UPC-E, Codabar

#### 2D

PDF 417, QR code, DATA MATRIX



### FONTS / GRAPHICS

#### Character Type

Font A(12x24), Font B(9x17),

Chinese(Traditional/Simplified, 24x24),

Korean(24x24), Japanese(24x24)

#### Characters per line (CPL)

Font A(12x24) : 42cpl,

Font B(9x17) : 56cpl,

#### Character set

95 Alphanumeric,

14 International,

128 x 18 Graphic



### ACCESSORIES

#### Standard

Power Adaptor 24Vdc / 1.75A

#### Option

Melody box, Spill proof cover

# sewoo

#### Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

#### USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA\_Sales@miniprnter.com

#### México

Cuahtémoc, Mexico D.F.

T. +52-1-55-143893 M. +52-1-55-3232-9543

E. LA\_Sales@miniprnter.com

