

sewoo

Compact size and Enhanced usability

SLK-TS400



- Structure for easy maintenance
- Design for enhanced usability
- Compact footprint to help easily fit on the counter.
- Ideal for front exit printing with Wall mount.
- Supports flexible printing exit way Front exit or top exit.
- Ideal for kitchen/bar printer with melody box(Kitchen buzzer)
- Easy handling the jam of the paper with same cover opening/closing direction as paper cutting direction.



Rugged Design



Compact Design



High Speed



Easy Maintenance



Various Interface




Barcode



Drop Resistant



Durable



Easy Loading



Paper Width

APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method
Direct thermal

Print Speed
Up to 8.6ips(220mm/sec)

Print Width
Up to 2.8" (72mm)

Resolution
180 dpi

Power
Power type : External SMPS
AC : 100~240Vac 50/60Hz
DC : 24Vdc / 1.75A

Sensor
Paper end, Cover open

Reliability
TPH life : 160km
MCBF : 60 Million lines
Cutter life : 2 Million cuts

Drawer port
2 circuits(24V, 1A Max.)



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)
5.1"×5.5"×6.0"
(130×140×154mm)

Weight
2.7lb(1.25Kg)



INTERFACES

Standard
USB(B type)+Serial
(RS-232C_25pin)Built-in,
USB(B type)+Ethernet Built-in

Optional
Wi-Fi(802.11a/b/g/n),
Bluetooth Smart Ready
(Bluetooth5.2+BLE)



CERTIFICATIONS

CE, FCC, KC, UL/cUL, CB,
ENERGY STAR, TELEC



OPERATING CHARACTERISTICS

Operating Temperature
32 ~ 113°F(0 ~ 45°C)

Operating Humidity
35 ~ 80%

Storage Temperature
-4 ~ 140°F(-20 ~ 60°C)

Storage Humidity
10 ~ 90%



MEDIA CHARACTERISTICS

Media Type
Thermal receipt paper

Media Width
3.14"(80mm)

Media Core Diameter
0.4"(12.5mm)

Media Roll Diameter
3.1"(ø 83mm)

Thickness
0.06~0.09mm



SOFTWARE

Emulations
ESC/POS

Drivers
Windows Driver(XP ~, Server2003 ~),
Windows CE & Mobile Driver (CE 4.2 ~,
Mobile 5.0 ~), Linux Driver, Mac Driver,
OPOS Driver, JavaPOS Driver, iOS SDK,
Android(6.0 ~) SDK, Windows SDK,
Windows CE SDK, Linux SDK



BARCODES

1D
EAN-8, EAN-13, Code 39, Code 93,
Code 128, ITF, UPC-A, UPC-E, Codabar

2D
PDF 417, QR code, DATA MATRIX



FONTS / GRAPHICS

Character Type
Font A(12x24), Font B(9x17),
Chinese(Traditional/Simplified, 24x24),
Korean(24x24), Japanese(24x24)

Characters per line (CPL)
Font A(12x24) : 42cpl,
Font B(9x17) : 56cpl,

Character set
95 Alphanumeric,
14 International,
128 x 18 Graphic



ACCESSORIES

Standard
Power Adaptor 24Vdc / 1.75A

Option
Melody box, 24V Buzzer

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA
T. +1-310-617-7401
E. NA_Sales@miniprnter.com

México

Cuahtémoc, Mexico D.F.
T. +52-1-55-143893 M. +52-1-55-3232-9543
E. LA_Sales@miniprnter.com

